



Specifications:

- Reliable shaded-pole motor construction
- Die-cast aluminum frame painted black for moisture and corrosion resistance.
- Injection molded impeller UL 94V-O rating.
- Precision, life lubricated ball bearing system.
- Insulation -Class B integral ground system rated @ 120 Deg C.
- Operation Temperature of -10 to +70 Deg C.
- Operation voltage for 115V, ranged from 85V to 125 V.
- Two year manufacturer warranty.
- Dimensions shown have a +/- 0.062" tolerance.

A1238H11S	
1. MODEL NUMBER	A1238H11S
2. CATEGORY	AXIAL AC FAN
3. FRAME SIZE	120 x 120x 38mm (4.7 x 4.7 x 1.5 inch)
4. RATED VOLTAGE	115 VAC
5. OPERATING VOLTAGE RANGE	100V ~125V
6. FREQUENCY	50/60 Hz
7. RATED MOTOR SPEED	2600/3000 RPM ±10%
8. AIR FLOW	95/115 CFM (2.69/3.26m ³ /Min.)
9. STATIC PRESSURE	6.8/8.5 mm/H ₂ O (0.27/0.33 inch/H ₂ O)
10. RATED CURRENT	0.30 Amp ±10%
11. RATED INPUT POWER	23/20 Watts ±10%
12. NOISE LEVEL	40/43 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-20°C ~ + 75°C / 66% (RH) ± 20%
15. STORAGE TEMPERATURE	-30°C ~ + 75°C / 66% (RH) ± 20%
16. BEARING SYSTEM	SLEEVE BEARING
17. LIFE EXPECTANCY	30,000 Hrs
18. FRAME MATERIAL	METAL W/ALUMINUM DIE-CASTING
19. IMPELLER MATERIAL	THERMOPLASTIC PBT OF UL 94V-0
20. LEAD WIRE	UL 1007, AWG#22
21. SAFETY	UL, CUL, TUV, CE
22. WEIGHT	540 gm



Item: Muffin Fan
Function: Ventilate Cabinet Interior
Mounting: Multiple locations include door, 'ceiling' of cabinet, and side panels
Features:
 -Small size allows for many possible mounting locations
 -Easy to mount with (4) fasteners
 -Can be mounted to both steel or laminate console construction
 NOTE: 55 CFM Fan also available (WCD-F100)

105 CFM Whisper Fan
WCD-F101/10705

Rev. 0 | 01/18/17 | V. Graves



Component Specification

QMF09a